



MX-SERIES 4141N/5140N

COPY • PRINT SCAN • FAX COLOR

ESSENTIAL SERIES DOCUMENT SYSTEMS



- Speeds of up to 41 (4141N) & 51 (5140N) ppm in black/white & color
- Full-size, retractable keyboard
- Powerful 1.8 GHz multi-processor
- Large 10.1" fully customizable color touchscreen display
- 1200 x 1200 DPI printing provides clear, crisp images
- Standard wireless connectivity for easy placement and mobility

SERVICING SOUTH FLORIDA FOR OVER 10 YEARS

COMPLETEOFFICE.CO

MX-4141N/5140N Specifications

Network Printing System

	Base models include multitasking controller, 100-sheet RSPF
5140N/5141N	(MX-4140N/5140N)/150-sheet DSPF (MX-4141N/5141N), PCL [®] 6 and Adobe [®] PostScript [®] 3 [™] printing systems, network scanning,
	auto duplexing, 2 x 500-sheet paper drawers, 100-sheet bypass
	tray. Black and color developer is included.
Туре	Color multi-function digital document system
Display	10.1" (diagonally measured) color dot matrix high-resolution touch
F	panel tilting display. 1024 x 600 dots (W-SVGA).
Functions	Copy, print, network print, network scan, document filing and fax ¹
Copy System	Dry electrostatic transfer/Dual component developer/Magnetic brush development/OPC drums/Belt type fusing/white LED exposure
Originals	Sheets and bound documents
Max Original Size	11" x 17"
Copy Size	Min. 5½" x 8½", Max. 11" x 17" + 12" x 18"
Copy Speed	41/51 ppm B&W/Color (8½" x 11")
Multiple Copy First Copy Time	Max. 999 copies MX-4140N MX-4141N MX-5140N MX-5141N
Seconds ²	Black Color Black Color Black Color Black Color
	Platen Glass 4.7 6.7 4.7 6.7 4.1 5.7 4.1 5.7
	Doc. Feeder 7.7 9.8 7.4 10.3 7.0 8.8 6.7 9.2
Warm Up Time	30 seconds or less ²
Magnification	25% to 400% in 1% increments (with document feeder 25%-200%)
Original Feed	MX-4140N/5140N: 100-sheet RSPF/MX-4141N/5141N: 150-sheet DSPF with original size detection.
Scan Speed	RSPF Copy/Scan: Up to 51 IPM ² simplex/20 IPM duplex
oban opood	DSPF Copy: Up to 85 IPM ² simplex (B&W)/51 IPM simplex (Color)
	DSPF Scan: Up to 170 IPM ² duplex (B&W/Color)
Original Sizes	5½" x 8½", 8½" x 11", 8½" x 11" R, 8½" x 14", 11" x 17"
Paper Capacity	Standard: 1,100 Sheets/Maximum: 6,600 Sheets
Paper Feed System	Standard: (2) 500-sheet paper drawer (letter/legal/ledger/statement
	size) and 100-sheet bypass tray (letter/legal/ledger/statement/ envelope size). Optional: Single or double drawer paper deck (500
	or 1,000 sheets), tandem paper drawer (2,000 sheets), letter/legal/
	ledger/statement size.
Paper Weights	Paper drawers: 16 lb. bond to 80 lb. cover. Other paper types include
and Types	plain, pre-printed, recycled, pre-punched, letterhead and color paper
	Bypass tray: 16-28 lb. bond (plain paper), 13-16 lb. bond (thin paper), 00 110 lb. court (based of the paper), 10-04 lb. band (Margarah (Cam 10)), 10-04 lb. court (Cam 10),
	80-110 lb. cover (heavy paper), 20-24 lb. bond (Monarch/Com-10 envelope), tab paper (letter). Also label paper, gloss paper, pre-printed
	recycled, pre-punched, letterhead, color paper and OHP film.
Duplexing	Standard automatic duplex copying and printing
CPU	Up to 1.8 GHz multi-processor design
Interface	RJ-45 Ethernet (10/100/1000Base-T), USB 2.0 (2 host ports, front
Momon	and rear), USB 2.0 (1 device port, rear) Standard 4 CP conv/orint (obacod)/Hard Dick Drive: 220 CP
Memory Hard Disk Drive	Standard 4 GB copy/print (shared)/Hard Disk Drive: 320 GB 320 GB
Copy Resolution	Scan: B&W/color: 600 x 600 dpi; Copy Output: B&W/color: 600 x 600 dp
Color Modes	Auto Color Selection (ACS), Full Color Mode, Monochrome (B/W)
Exposure Control	Modes: Automatic, Text, Text/Photo, Text/Printed-Photo, Printed-Photo
	Photo, Map, Pale-Color Document. Settings: Auto or 9 step manual
Halftone	256 gradations/2 levels (monochrome)
Copy Features	Scan-Once Print-Many, electronic sorting, offset-stacking, Auto Colo Selection (ACS), Auto Paper Selection (APS), Auto Magnification
	Selection (AMS), Auto Tray Switching (ATS), black-white reversal,
	blank page skip, book copy, book divide, card shot, center erase,
	centering, cover pages, dual page copy, edge erase, image edit,
	image preview, insert pages, job build, job programs, margin shift,
	mirror image, mixed size original, multi-page enlargement, original
	count, pamphlet style, proof copy, repeat layout, reserve copy, rotated copy, stamp, stamp custom image, suppress background, tab copy,
	tab-paper insertion, tandem copy, toner save mode, transparency
	inserts, watermark, 2-in-1 / 4-in-1 / 8-in-1 multi shot
Account Control	Up to 1,000 users. Supports user-number authentication, login
	name/password or login name/LDAP password
Output Tray	Main output tray (top): 400 sheets (face down); optional right side
Capacity	exit tray: 100 sheets (face down) Elash ROM with local (USB), network undate capability and firmware
Firmware Management	Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Manager)
Device Setup	Web-based management/cloning with user/administrator level login
Service/Functions	Remote front panel, remote access to service logs and click counts
Accessibility	Tilt front panel, adjustment of key touch sound and speed, concave
Features	key, document feeder free stop, job programs, remote front panel,
Environmentel	universal grip for paper trays, and disable screen timeout
Environmental Standards	International Energy Star Program Ver. 2.0, Canadian EcoLogo Program (CCD-035), Blue Angel (RAL-UZ171), European RoHS
Power	AC 100-127 VAC, 60 HZ, 16 Amps
Power Consumption	
Weight	MX-4140N/5140N: Approx. 262 lbs./MX-4141N/5141N: 278 lbs.

¹ Some features require optional equipment. See your local dealer.

² May vary depending on product configuration, machine settings and operating and/or environmental conditions.

³ Actual transmission time will vary based on line conditions. ⁴ Based on Sharp Standard Test Chart with approximately 700 characters, letter size in standard resolution.

Network Printing	
PDL	Standard PCL [®] compatible 6, PostScript [®] 3™, optional XPS
Resolution	1200 x 1200 dpi
Print Speed	41/51 pages per minute (8½" x 11")
Print Drivers	Windows XP, Windows XP x64, Windows Server® 2003, Windows
	Server® 2003 x64, Windows Server® 2008, Windows Server 200
	x64, Windows Vista®, Windows Vista x64, Windows 7, Windows
	7 x64, Windows 8, Windows 8 x64, Windows Server 2012 x64,
	Windows PPD, MAC OSX® (including 10.4 to 10.8), all MAC PPD
Features	Auto configuration, bar code font printing, carbon copy print, chap
	inserts, color adjustment settings, color mode, confidential print,
	continuous printing, custom image registration, different cover page
	last page/other page, document control, document filing, duplex
	printing, electronic sorting, folding, form overlay, hidden pattern
	print, image rotation, image stamp, image type, job bypass print,
	job retention, layout print, margin shift, multiple pamphlet, network
	tandem print, N-up printing, offset stacking, page interleave,
	pamphlet style, poster print, proof print, print and send, print mod
	punching, stapling, tab paper print, tab printing, toner save mode,
	transparency inserts, tray status, user authentication, watermarks,
	zoom print ¹
Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Compact PDF, Encrypte
	PDF, PostScript and XPS.1
Desta de la	Methods: FTP, SMB, Web page, E-mail and USB memory
Resident Fonts	80 outline fonts (PCL), 139 fonts (PS)
Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0
Operating Systems	Windows Server 2003, Windows Server 2008, Windows XP,
	Windows Vista, Windows Systems 7, Windows 8, Mac OS X10.4,
	X10.5, X10.6, X10.7, X10.8, Novell® NetWare®, UNIX®, Linux® an
	Citrix [®] (XenApp 5.0, 6.0, 6.5) and Windows Terminal Services, SA device types ¹
Network Protocols	TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, SMTP,
NELWOIK FIOLOGOIS	POP3, LDAP, 802.1x for Windows and Unix. LPD and LPR for
	Unix. IPX/SPX® for Novell environments. EtherTalk®. AppleTalk® for
	Macintosh® environments.1
Printing Protocols	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP, POP3, HTTP, and
	Novell Pserver/Rprinter
Network Security	IP/MAC address filtering, protocol filtering, port management, use
,	authentication and document administration1
Security Standards	IEEE-2600 [™] -2008, DoD (NSTISSP) #11, CAC/PIV access control ¹
Network Scanning	
Scan Modes	Standard: Color, monochrome, grayscale
Max Original Size	11" x 17"
Optical Resolution	600 dpi
Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Image Formats	Monochrome: TIFF, PDF, PDF/A, Encrypted PDF, XPS
	Color: Grayscale, Color TIFF, JPEG, PDF, PDF/A, Compact PDF,
	Encrypted PDF, XPS; Internet Fax: TIFF-FX, TIFF-F, TIFF-S1
Image	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR)
Compression	Color/Grayscale: JPEG (high, middle, low)
Coop Doctination-	Internet Fax mode: MH/MMR (option)
Scan Destinations	E-mail, Desktop, FTP, Folder (SMB), USB, Internet fax (option),
One-touch	Super G3 fax (option)
One-touch	Up to 2,000 (combined scan destinations)
Destinations Group Destinations	Lip to 500
Group Destinations	
Programs Max. Jobs	48 (combined) Up to 100
Network Protocols	
NOTWORK FILLOUD	TCP/IP and SSL (includes HTTP, SMTP, LDAP, FTP, POP3), SMB, ESMTP and 802.1x
Network Security	E-mail server user authentication for LDAP and Active Directory
Software	Sharpdesk [®] desktop personal document management software
Gontware	(1 user license included), Sharpdesk Mobile (download)
B&W Super G3 Fa	x Kit (option)
Transmission Mode	
Modem Speed	33.6 KBPS ³
Compression	JBIG, MMR, MR, MH
Methods	
Scanning Method	Sheet fed simplex or duplex or book
Max. Resolution	400 dpi
Wax. Hesolution	

Transmission would	Super do, do
Modem Speed	33.6 KBPS ³
Compression	JBIG, MMR, MR, MH
Methods	
Scanning Method	Sheet fed simplex or duplex or book
Max. Resolution	400 dpi
Transmit Speed	Approx. 2 seconds with Super G3/JBIG ⁴
Auto Dialing	Up to 2,000 (combined scan destinations)
Group Dial	Up to 500 destinations
Inbound Fax Routing	Forwards received fax data to E-mail, FTP, SMB, Desktop, Fax, I-Fax ¹
Long Origina l s	Up to 33 1/4" (for transmission)
Programs	48 (combined)
Memory	1 GB
Halftone	256 levels



ImageSEND

SHARP



1K Saddle Stitch Finisher (option) Console finisher with dual exit trays (mounts on left side Туре of host machine) Output Trays Upper tray: Offset stack tray Lower tray: Book tray for saddle stitch Output Capacity 1,000 sheets (letter/statement size) or 500 sheets (legal, ledger, letter) Sta

	(legal, leuger, letter)
Stapling	Up to 50 sheets (letter/statement) or 25 sheets
	(legal, ledger or mixed)
Output Delivery	Face down
Stapling Media	Plain paper, letter/legal/ledger size or mixed
Stapling Positions	1 front, 1 rear, or both
Saddle Stitch	Center stitch/center folding (2 staples)
Function	letter/legal/ledger paper sizes
Saddle Stitch	Up to 10 sets (11-15 sheets per set)/15 sets
Max. Sets	(6-10 sheets per set)/20 sets (1-5 sheets per set)
Power	Approx. 70 W or less (MX-FN10)/138 W or less (MX-FN18)
Consumption	
Hole Punching	Optional three-hole punch unit MX-PNX5B (MX-FN10)/
	MX-PNX6B (MX-FN18)
Weight	Approx. 88 lbs. (MX-FN10)/Approx. 161 lbs. (MX-FN18)
Dimensions	MX-FN10 (with tray extended): Approx. 26" (w) x 25" (d) x 39" (h)
	MX-FN18 (with tray extended): Approx. 30" (w) x 25" (d) x 44" (h)
4K Stacking Finis	her (option)
Туре	Console stacking finisher with dual exit trays
	(mounts on left side of host machine)
Output Trays	Fixed position upper tray and offset stacking lower tray
Output Capacity	Upper tray: 1,550 sheets (letter size, non-stapled)
	Lower tray: 2,450 sheets (letter size, non-stapled)
Stapling	Three position; Up to 50 sheets (letter/statement)
Power Consumptio	n Approx. 140 W
Hole Punching	Optional three-hole punch unit MX-PNX6B

Weight	Approx. 97 lbs.
Dimensions	(MX-FN11): Approx. 20" (w) x 25" (d) x 43" (h)

Optic	onal	Equip	me

Optional Equip	ment		
MX-DE21	Stand + 2,000-sheet Tandem Paper Drawer		
MX-DE22	Stand/1 x 500 Sheet Paper Drawer		
MX-DE23	Stand/2 x 500 Sheet Paper Drawer		
MX-DS18	Deluxe Copier Cabinet		
MX-LC11	Large Capacity Tray (requires MX-DS18/DE21/22/23)		
MX-LT10	Long Paper Feeding Tray		
MX-FNX9	Inner Finisher		
MX-PNX1B	3-Hole Punch Unit (requires MX-FNX9)		
MX-FN10	1K Saddle Stitch Finisher		
MX-PNX5B	3-Hole Punch Unit (requires MX-FN10)		
MX-FN11	4K Stacking Finisher		
MX-FN18	4K Saddle Stitch Finisher		
MX-PNX6B	3-Hole Punch Unit (requires MX-FN11/18)		
MX-RB20	Paper Pass Unit (required for MX-FN10/11/18)		
MX-SCX1	Staple Cartridge (5,000 staples) (requires MX-FNX9/FN10)		
AR-SC2	Staple Cartridge (5,000 staples) (requires MX-FN11/18)		
AR-SC3	Staple Cartridge (2,000 staples) (requires MX-FN10/18)		
MX-TRX2	Right Exit Tray		
MX-TU13	Center Exit Tray		
MX-PUX1	XPS Expansion Kit		
MX-FX11	Fax Expansion Kit		
MX-FWX1	Internet Fax Kit		
MX-PF10	Bar Code Font Kit		
AR-SU1	Stamp Unit (requires AR-SV1 Stamp Cartridge)		
AR-SV1	Stamp Cartridge		
MX-KB11N	Keyboard (standard on the MX-4141N/5141N)		
MX-EB11	Compact PDF Kit (standard on the MX-4141N/5141N)		
MX-EB12N	Mirror Expansion Kit		
MX-EC50	CAC Reader (requires Data Security Kit)		
MX-AMX1	Application Integration Module		
MX-AM10	Web Browsing Expansion Kit (standard on the MX-5141N)		
MX-FR42U	Commercial Data Security Kit		
DVENDPS	Generic Vendor Interface Kit		



